

Lynx-TE Amalgam

SA CFTE 32W/840 GX24Q-3 AMALGA

0027840



Range features

- Excellent luminous flux at high and low ambient temperatures
- Particularly suitable for use in the new generation of ultra compact fluorescent downlights and luminaires
- Amalgam technology designed for high temperature applications
- Excellent colour rendering - (CRI=85)
- To be operated on electronic ballasts only
- Dimmable with suitable dimmer
- Available in Warm White (3000K) and Cool White (4000K)
- Average rated life: 12000 hours



PRODUCT OVERVIEW

Light colour	840 Cool White
Ordering number	0027840
Technology	Compact Fluorescent
Energy class	A
Lamp shape	Stick
Lamp finish	Frosted
Dimmable	yes
Cap/Base	GX24q-3
Type	Lynx TE
EAN code	5410288278407
CRI (Ra)	82
Colour temperature (K)	4000
Luminous flux (Rated) (lm)	2400
Watt (Nominal) (W)	32
Voltage (V)	100

Lynx-TE Amalgam

SA CFTE 32W/840 GX24Q-3 AMALGA

0027840

DATA TABLE

Lynx-TE Amalgam

SA CFTE 32W/840 GX24Q-3 AMALGA

0027840

General data

Ordering number	0027840
Technology	Compact Fluorescent
Average life (Nominal) (h)	12000
Energy class	A
Lamp finish	Frosted
Lamp shape	Stick
Dimmable	yes
Cap/Base	GX24q-3
Type	Lynx TE
EAN code	5410288278407
E-number FI	4944074
E-number SE	8357423
Long description	Excellent luminous flux at high and low ambient temperatures. Particularly suitable for use in the new generation of ultra compact fluorescent downlights and luminaires. Amalgam technology designed for high temperature applications. Excellent colour rendering - (CRI=85). To be operated on electronic ballasts only. Dimmable with suitable dimmer. Available in Warm White (3000K) and Cool White (4000K). Average rated life: 12000 hours
Product name	SA CFTE 32W/840 GX24Q-3 AMALGA
Lamp mercury content (mg)	1.3
Starting time (max) (s)	0.1
Warm-up time to 60% of full light (max) (s)	60
Control gear required	Yes
Fixture rating	Open
IEC Reference	IEC 60901
IEC Reference 2	IEC 61199
Intended purpose	General lighting
Special purpose lamp	No
Transformer required	No
Sales pack quantity	10
Rated survival factor at 2000 h 50Hz	0,99*
Rated survival factor at 2000 h High Frequency	> 0.99
Rated survival factor at 4000 h 50Hz	0,99*
Rated survival factor at 4000 h High Frequency	> 0.98
Rated survival factor at 6000 h 50Hz	0,99*
Rated survival factor at 6000 h High Frequency	> 0.95
Rated survival factor at 8000 h 50Hz	0,99*
Rated survival factor at 8000 h High Frequency	> 0.92
Rated survival factor at 12000 h 50Hz	0,96*
Rated survival factor at 16000 h	> 88%
Rated survival factor at 16000 h High Frequency	> 0.80
Rated survival factor at 20000 h High Frequency	> 0.50

Lynx-TE Amalgam

SA CFTE 32W/840 GX24Q-3 AMALGA

0027840

Optical data

Light colour	840 Cool White
CRI (Ra)	82
Colour temperature (K)	4000
Luminous flux (Nominal) (lm)	2400
Luminous flux (Rated) (lm)	2400
Ambient temperature for maximum luminous flux (°C)	25
Rated lumen maint. factor at 2000 h 50Hz	0,94*
Rated lumen maint. factor at 4000 h 50Hz	0,91*
Rated lumen maint. factor at 6000 h 50Hz	0,89*
Rated lumen maint. factor at 8000 h 50Hz	0,87*
Rated lumen maint. factor at 12000 h 50Hz	0,84*
Rated lumen maint. factor at 2000 h High Frequency	> 0.92
Rated lumen maint. factor at 4000 h High Frequency	> 0.88
Rated lumen maint. factor at 6000 h High Frequency	> 0.86
Rated lumen maint. factor at 8000 h High Frequency	> 0.84
Rated lumen maint. factor at 12000 h High Frequency	> 0.80
Rated lumen maint. factor at 16000 h High Frequency	> 0.78
Rated lumen maint. factor at 20000 h High Frequency	> 0.75

Electrical data

kWh per 1000 hours burning time	35
Rated lamp efficacy (lm/W) 100H 50Hz at optimum temp.	75
Watt (Rated) (W)	32
Watt (Nominal) (W)	32
Voltage (V)	100
Ignition voltage (V)	0
Current (A)	0.32

Lynx-TE Amalgam

SA CFTE 32W/840 GX24Q-3 AMALGA

0027840

Physical data


Weight (kg)	0.09
Length base to base (mm) - A	141.2
Lamp Length (mm) - C/L	145
Max. Lamp Diameter (mm) - D	49.3
Single packaging type	Box/Sleeve
Single package dimensions (L x W x H) (cm)	5.10 x 4.70 x 17.20
Outer package dimensions (L x W x H) (cm)	26.70 x 10.30 x 18.60

Lynx-TE Amalgam

SA CFTE 32W/840 GX24Q-3 AMALGA

0027840

TECHNICAL DRAWINGS



ENERGY LABEL

